

1. Identification

Product identifier DIESEL NO. 1 PRODUCTS (UNBRANDED)

Other means of identification

SDS number 10124

Synonym(s) APPLICABLE TO ALL GRADES OF DIESEL OIL NO. 1; INCLUDING ULTRA LOW SULFUR DIESEL (S15), * BIODIESEL BLENDS (< OR = 5%), KEROSENE PRODUCTS, * HEATING OIL AND GOLD® DIESEL PRODUCTS.

Recommended use Motor Fuel

Recommended restrictions Other uses are not recommended unless an assessment is completed, prior to commencement of that use, which demonstrates that the use will be controlled.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Supplier

Fauser Energy Resources
 106 Center St
 Elgin, IA 52141
 United States

Telephone numbers – 24 hour emergency assistance

800-328-7371

Telephone numbers – general assistance

8-5 (M-F, CST) MSDS Assistance 563-426-5811

Email:

resources@fauserenergy.com

2. Hazard(s) identification

| | | |
|------------------------------|--|-----------------------------|
| Physical hazards | Flammable liquids | Category 3 |
| Health hazards | Skin corrosion/irritation | Category 2 |
| | Specific target organ toxicity, single exposure | Category 3 narcotic effects |
| | Aspiration hazard | Category 1 |
| OSHA defined hazards | Not classified. | |
| Environmental hazards | Hazardous to the aquatic environment, acute hazard | Category 2 |
| | Hazardous to the aquatic environment, long-term hazard | Category 2 |

Label elements



Signal word

Danger

Hazard statement

Flammable liquid and vapor. Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment.

| | |
|--|--|
| Response | If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Specific treatment (See first aid instructions on this label). In case of fire: Use water spray, dry chemical, carbon dioxide or fire-fighting foam for Class B to extinguish. Collect spillage. Take off contaminated clothing and wash before reuse. |
| Storage | Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up. |
| Disposal | Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Hazard(s) not otherwise classified (HNOC) | Static accumulating flammable liquids Classified |
| Supplemental information | |
| Hazard statement | Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion. |
| Prevention | Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. These alone may be insufficient to remove static electricity. |
| Response | Eliminate all ignition sources if safe to do so. |

3. Composition/information on ingredients

| Components | Common name and synonyms | CAS number | % |
|---|--------------------------|------------|-----------|
| KEROSENE (PETROLEUM), HYDRODESULFURIZED | | 64742-81-0 | 0 - 100 % |
| KEROSENE, STRAIGHT RUN | | 8008-20-6 | 0 - 100 % |

Additional components

| Chemical name | CAS number | % |
|------------------------|------------|---------|
| BIODIESEL | Mixture | 0 - 7 |
| 1,2,4-TRIMETHYLBENZENE | 95-63-6 | 0 - 6 |
| ETHYLBENZENE | 100-41-4 | 0 - 4 |
| TOLUENE | 108-88-3 | 0 - 2 |
| XYLENE | 1330-20-7 | 0 - 1 |
| NAPHTHALENE | 91-20-3 | 0 - 0.5 |
| BIPHENYL | 92-52-4 | 0 - 0.5 |
| CUMENE | 98-82-8 | 0 - 0.3 |
| BENZENE | 71-43-2 | < 0.1 |

Composition comments Values do not reflect absolute minimums and maximums; these values are typical which may vary from time to time.

This Safety Data Sheet is intended to communicate potential health hazards and potential physical hazards associated with the product(s) covered by this sheet, and is not intended to communicate product specification information. For product specification information, contact your Fauser Energy Resources representative.

4. First-aid measures

Inhalation

Remove to fresh air. If not breathing, institute rescue breathing. If breathing is difficult, ensure airway is clear and give oxygen. If heart has stopped, immediately begin cardiopulmonary resuscitation (CPR).

Keep affected person warm and at rest. GET IMMEDIATE MEDICAL ATTENTION.

Skin contact

Immediately wash skin with plenty of soap and water after removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.

Place contaminated clothing in closed container for storage until laundered or discarded. If clothing is to be laundered, inform person performing operation of contaminant's hazardous properties. Discard contaminated leather goods.

Eye contact

Flush immediately with large amounts of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Get medical attention if irritation persists.

| | |
|---|---|
| Ingestion | Do not induce vomiting because of danger of aspirating liquid into lungs, causing serious damage and chemical pneumonitis. If spontaneous vomiting occurs, keep head below hips to prevent aspiration and monitor for breathing difficulty. Never give anything by mouth to an unconscious person. |
| Most important symptoms/effects, acute and delayed | <p>Keep affected person warm and at rest. GET IMMEDIATE MEDICAL ATTENTION.</p> <p>INHALATION: May cause central nervous system depression or effects. Symptoms may include headache, excitation, euphoria, dizziness, incoordination, drowsiness, light-headedness, blurred vision, fatigue, tremors, convulsions, loss of consciousness, coma, respiratory arrest and death, depending on the concentration and duration of exposure.</p> <p>Breathing of the mists, vapors or fumes may irritate the nose, throat and lungs.</p> <p>SKIN: Contact may cause reddening, itching and inflammation. Prolonged skin contact may defat the skin and cause drying, cracking and/or dermatitis. Skin contact may cause harmful effects in other parts of the body.</p> <p>EYES: May cause eye irritation with tearing, redness, or a stinging or burning sensation. May cause swelling of the eyes with blurred vision. Effects may become more serious with repeated or prolonged contact.</p> <p>INGESTION: May cause irritation of the mouth, throat and gastrointestinal tract. Symptoms may include salivation, pain, nausea, vomiting and diarrhea.</p> <p>Aspiration into lungs may cause chemical pneumonia and lung damage.</p> |
| Indication of immediate medical attention and special treatment needed | <p>INHALATION: This material (or a component) sensitizes the myocardium to the effects of sympathomimetic amines. Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmias in individuals exposed to this material. Administration of sympathomimetic drugs should be avoided.</p> <p>INGESTION: If ingested this material represents a significant aspiration and chemical pneumonitis hazard. Induction of emesis is not recommended.</p> |
| 5. Fire-fighting measures | |
| Suitable extinguishing media | Use water spray, dry chemical, carbon dioxide or fire-fighting foam for Class B fires to extinguish fire. |
| Unsuitable extinguishing media | Do not use a solid water stream as it may scatter and spread fire. |
| Specific hazards arising from the chemical | <p>Combustion may produce CO_x, NO_x, SO_x, reactive hydrocarbons, irritating vapors, and other decomposition products in the case of incomplete combustion.</p> <p>Extremely flammable. Vapors form flammable or explosive mixtures with air at room temperature. Vapor or gas may spread to distant ignition sources and flash back.</p> <p>Static accumulator (nonconductive) flammable or combustible material may form ignitable vapor-air mixtures in storage tanks. Bonding and grounding may be insufficient to eliminate the hazard from static accumulation.</p> <p>Explosion hazard if exposed to extreme heat.</p> |
| Special protective equipment and precautions for firefighters | <p>Evacuate area and fight fire from a safe distance.</p> <p>If leak or spill has not ignited, ventilate area and use water spray to disperse gas or vapor, cool adjacent structures, and to protect personnel attempting to stop a leak.</p> <p>Shut off source of flow, if possible.</p> <p>Stay away from storage tank ends. Withdraw immediately in case of rising sound from venting safety device or any discoloration of storage tank due to fire. Always stay away from tanks engulfed in flame.</p> <p>Firefighters must wear NIOSH approved positive pressure breathing apparatus (SCBA) with full face mask and full protective equipment.</p> |

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary people away; isolate hazard area and deny entry. For spills in confined areas, ensure adequate ventilation. For spills outdoors, stay upwind. IF TANK, RAILCAR OR TANK TRUCK IS INVOLVED IN A FIRE, isolate for 800 meters (1/2 mile) in all directions. Evacuate area endangered by release as required. Wear appropriate personal protective equipment. See Exposure Controls/Personal Protection (Section 8).

Methods and materials for containment and cleaning up

Keep unnecessary people away. Isolate area for at least 50 meters (164 feet) in all directions to preserve public safety. For large spills, if downwind consider initial evacuation for at least 300 meters (1000 feet).

Small Spills: Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Large Spills: Dike far ahead of liquid spill for later disposal. Avoid clean up procedures that may result in water pollution.

Do not touch or walk through spilled material. Stop leak when safe to do so.

See Exposure Controls/Personal Protection (Section 8).

Environmental precautions

Prevent entry into water ways, sewers, basements or confined areas. Notify local authorities and National Response Center, if required.

If the material is spilled or allowed to leak from storage or containment it can contaminate soil and ground water. Ensure the storage or containment equipment is suitable for safely holding this material.

7. Handling and storage

Precautions for safe handling

Electrostatic charge may accumulate and create a hazardous condition when handling this material.

Static accumulator (nonconductive) flammable or combustible material may form ignitable vapor-air mixtures in storage tanks. Bond and ground lines and equipment (tank, transfer lines, pump, floats, etc.) used during transfer to reduce the possibility of static spark-initiated fire or explosion.

Review all operations which have the potential of generating and accumulating an electrostatic charge and/or a flammable atmosphere (such as tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate procedures to mitigate the hazard.

Bonding and grounding may be insufficient to eliminate the hazard from static accumulation. Additional precautions should be considered consistent with the current NFPA 77, Recommended Practice on Static Electricity, the current API Recommended Practice 2003, Protection Against Ignitions Arising Out of Static, Lightning, and Stray Currents and OSHA Standard 29 CFR 1910.106, Flammable and Combustible Liquids.

Use non-sparking tools. Do not use electronic devices while handling, unless the device is certified as intrinsically safe as they could present ignition sources.

Avoid contact with strong oxidizing agents. Prevent small spills to minimize slip hazard or release to the environment. Do not cut, grind, drill, weld (or introduce any other ignition source) on empty containers. Do not reuse containers unless adequate precautions are taken.

Avoid personal contact with this material. Always observe good personal hygiene measures, such as removing contaminated clothing and protective equipment, washing after handling the material and before entering public areas. Restrict eating, drinking and smoking to designated areas to prevent personal chemical contamination. Routinely wash work clothing and protective equipment to remove contaminants. Do not breathe mist or vapor.

Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in a cool, dry, isolated, well-ventilated area away from heat, sources of ignition and incompatibles. Ground/bond container and equipment. Avoid contact with strong oxidizing agents. Empty containers may contain material residue. Do not reuse without adequate precautions.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

| Additional components | Type | Value |
|--------------------------|------|-------|
| BENZENE (CAS 71-43-2) | STEL | 5 ppm |

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

| Additional components | Type | Value |
|------------------------------|-------------|--------------|
| | TWA | 1 ppm |

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Additional components | Type | Value |
|--------------------------------|-------------|--------------|
| XYLENE (CAS 1330-20-7) | TWA | 100 ppm |
| NAPHTHALENE (CAS 91-20-3) | PEL | 10 ppm |
| ETHYLBENZENE (CAS 100-41-4) | TWA | 100 ppm |
| BIPHENYL (CAS 92-52-4) | TWA | 0.2 ppm |
| CUMENE (CAS 98-82-8) | TWA | 50 ppm |

US. OSHA Table Z-2 (29 CFR 1910.1000)

| Additional components | Type | Value |
|------------------------------|-------------|--------------|
| TOLUENE (CAS 108-88-3) | Ceiling | 300 ppm |
| | TWA | 200 ppm |
| BENZENE (CAS 71-43-2) | TWA | 1 ppm |

U.S. - Minnesota (MNOSHA)

| Additional components | Type | Value |
|--|-------------|--------------|
| TOLUENE (CAS 108-88-3) | STEL | 150 ppm |
| | TWA | 100 ppm |
| XYLENE (CAS 1330-20-7) | STEL | 150 ppm |
| | TWA | 100 ppm |
| NAPHTHALENE (CAS 91-20-3) | STEL | 15 ppm |
| | TWA | 10 ppm |
| ETHYLBENZENE (CAS 100-41-4) | STEL | 125 ppm |
| | TWA | 100 ppm |
| BIPHENYL (CAS 92-52-4) | TWA | 0.2 ppm |
| 1,2,4-TRIMETHYL BENZENE (CAS 95-63-6) | TWA | 25 ppm |
| CUMENE (CAS 98-82-8) | TWA | 50 ppm |
| BENZENE (CAS 71-43-2) | STEL | 5 ppm |
| | TWA | 1 ppm |

US. ACGIH Threshold Limit Values

| Components | Type | Value | Form |
|--|-------------|--------------|-------------|
| KEROSENE (PETROLEUM) , HYDRODESULFURIZED (CAS 64742-81-0) | TWA | 200 mg/m3 | Skin; P |
| KEROSENE, STRAIGHT RUN (CAS 8008-20-6) | TWA | 200 mg/m3 | Skin; P |
| Additional components | Type | Value | Form |
| TOLUENE (CAS 108-88-3) | TWA | 20 ppm | |
| XYLENE (CAS 1330-20-7) | STEL | 150 ppm | |
| | TWA | 100 ppm | |

US. ACGIH Threshold Limit Values

| Additional components | Type | Value | Form |
|---------------------------------------|------|---------|------|
| NAPHTHALENE (CAS 91-20-3) | TWA | 10 ppm | Skin |
| ETHYLBENZENE (CAS 100-41-4) | STEL | 125 ppm | |
| | TWA | 20 ppm | |
| BIPHENYL (CAS 92-52-4) | TWA | 0.2 ppm | |
| 1,2,4-TRIMETHYL BENZENE (CAS 95-63-6) | TWA | 25 ppm | |
| CUMENE (CAS 98-82-8) | TWA | 50 ppm | |
| BENZENE (CAS 71-43-2) | STEL | 2.5 ppm | Skin |
| | TWA | 0.5 ppm | Skin |

US. NIOSH: Pocket Guide to Chemical Hazards Components

| Components | Type | Value |
|--|------|-----------|
| KEROSENE (PETROLEUM), HYDRODESULFURIZED (CAS 64742-81-0) | TWA | 100 mg/m3 |
| KEROSENE, STRAIGHT RUN (CAS 8008-20-6) | TWA | 100 mg/m3 |

| Additional components | Type | Value |
|---------------------------------------|------|---------|
| TOLUENE (CAS 108-88-3) | STEL | 150 ppm |
| | TWA | 100 ppm |
| XYLENE (CAS 1330-20-7) | STEL | 150 ppm |
| | TWA | 100 ppm |
| NAPHTHALENE (CAS 91-20-3) | STEL | 15 ppm |
| | TWA | 10 ppm |
| ETHYLBENZENE (CAS 100-41-4) | STEL | 125 ppm |
| | TWA | 100 ppm |
| BIPHENYL (CAS 92-52-4) | TWA | 0.2 ppm |
| 1,2,4-TRIMETHYL BENZENE (CAS 95-63-6) | TWA | 25 ppm |
| CUMENE (CAS 98-82-8) | TWA | 50 ppm |
| BENZENE (CAS 71-43-2) | STEL | 1 ppm |
| | TWA | 0.1 ppm |

Biological limit values**ACGIH Biological Exposure Indices**

| Additional components | Value | Determinant | Specimen | Sampling Time |
|-----------------------------|-----------|---|---------------------|---------------|
| TOLUENE (CAS 108-88-3) | 0.3 mg/g | o-Cresol, with hydrolysis | Creatinine in urine | * |
| | 0.03 mg/l | Toluene | Urine | * |
| | 0.02 mg/l | Toluene | Blood | * |
| XYLENE (CAS 1330-20-7) | 1.5 g/g | Methylhippuric acids | Creatinine in urine | * |
| ETHYLBENZENE (CAS 100-41-4) | 0.15 g/g | Sum of mandelic acid and phenylglyoxylic acid | Creatinine in urine | * |
| BENZENE (CAS 71-43-2) | 25 µg/g | S-Phenylmercapturic acid | Creatinine in urine | * |

* - For sampling details, please see the source document.

Exposure guidelines

US ACGIH Threshold Limit Values: Skin designation

| | |
|--|-----------------------------------|
| BENZENE (CAS 71-43-2) | Can be absorbed through the skin. |
| KEROSENE (PETROLEUM), HYDRODESULFURIZED (CAS 64742-81-0) | Can be absorbed through the skin. |
| KEROSENE, STRAIGHT RUN (CAS 8008-20-6) | Can be absorbed through the skin. |
| NAPHTHALENE (CAS 91-20-3) | Can be absorbed through the skin. |

US OSHA Specifically Regulated Substances: Action level and Reference

| | |
|-----------------------|---------|
| BENZENE (CAS 71-43-2) | 0.5 PPM |
|-----------------------|---------|

US OSHA Table Z-1: Skin designation

| | |
|----------------------|-----------------------------------|
| CUMENE (CAS 98-82-8) | Can be absorbed through the skin. |
|----------------------|-----------------------------------|

US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants

| | |
|--------------------------------------|--------------------|
| 1,2,4-TRIMETHYLBENZENE (CAS 95-63-6) | 125 MGM3 - 25 PPM |
| BENZENE (CAS 71-43-2) | 1 PPM |
| BIPHENYL (CAS 92-52-4) | 1.5 MGM3 - 0.2 PPM |
| CUMENE (CAS 98-82-8) | 245 MGM3 - 50 PPM |
| ETHYLBENZENE (CAS 100-41-4) | 22 MGM3 - 5 PPM |
| NAPHTHALENE (CAS 91-20-3) | 50 MGM3 - 10 PPM |
| TOLUENE (CAS 108-88-3) | 37 MGM3 - 10 PPM |
| XYLENE (CAS 1330-20-7) | 435 MGM3 - 100 PPM |

Appropriate engineering controls

Consider the following when employing engineering controls and selecting personal protective equipment: potential hazards of the material, applicable exposure limits, job activities, and other substances in the work place. Explosion-proof ventilation and other forms of engineering controls are the preferred means for controlling exposures below occupational exposure limits and guidelines.

Individual protection measures, such as personal protective equipment

Eye/face protection

Keep away from eyes. Eye contact can be avoided by using chemical safety glasses, goggles and/or face shield. Have eye washing facilities readily available where eye contact can occur.

Hand protection

Avoid skin contact with this material. Use chemical resistant gloves when handling this material. Contact the glove manufacturer for specific advice on glove selection regarding permeability and breakthrough times for your use conditions. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Other

Dermal exposure to this chemical may add to the overall exposure.

Respiratory protection

Avoid skin contact with this material. Additional protective clothing may be necessary.

A NIOSH approved air purifying respirator with an appropriate cartridge or canister, such as an organic vapor cartridge, may be used in circumstances where airborne organic vapor concentrations may exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection. See OSHA 29 CFR 1910.134 for more information regarding respiratory protection and Assigned Protection Factors (APFs).

Thermal hazards

No special precautions required.

9. Physical and chemical properties

Appearance

Physical state

Liquid.

Form

Not applicable

Color

Crystal clear; for tax exempt purposes, this fuel may contain red dye

Odor

Kerosene-like

Odor threshold

Not available.

pH

Essentially neutral

Melting point/freezing point

Not available / < -40 °F (< -40 °C)

Initial boiling point and boiling range

> 280 °F (> 137.8 °C)

Flash point

> 100 °F (> 37.78 °C) TCC (ASTM D56)

Evaporation rate

Very slow

Flammability (solid, gas)

Not applicable.

Upper/lower flammability or explosive limits

| | |
|---------------------------------------|------------------------|
| Flammability limit - lower (%) | 0.7 % |
| Flammability limit - upper (%) | 5 % |
| Explosive limit - lower (%) | See flammability limit |
| Explosive limit - upper (%) | See flammability limit |

Vapor pressure 22 mmHg at 158 °F (70 °C)

Vapor density 4.5 (Air = 1)

Relative density Not available.

Solubility(ies) Negligible

Partition coefficient (n-octanol/water) Not available

Auto-ignition temperature > 400 °F (> 204.44 °C)

Decomposition temperature Not available.

Viscosity 8 cSt at -4 °F (-20 °C)

Other information

| | |
|---------------------------------|---------------------------------------|
| Chemical family | Petroleum hydrocarbon |
| Electrostatic properties | |
| Conductivity | <= 50 pS/m |
| Percent volatile | 100 % |
| Specific gravity | 0.77 - 0.84 at 60/60 °F (15.6/15.6°C) |

10. Stability and reactivity

Reactivity See statements below.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions Not anticipated under normal conditions.

Conditions to avoid Avoid unventilated areas, heat, open flames, sparks and ungrounded electrical equipment.

Incompatible materials Incompatible with strong oxidizing agents. See precautions under Handling & Storage (Section 7).

Hazardous decomposition products Not anticipated under normal conditions.

11. Toxicological information

Information on likely routes of exposure

| | |
|---------------------|--------------------------|
| Ingestion | Likely route of exposure |
| Inhalation | Likely route of exposure |
| Skin contact | Likely route of exposure |
| Eye contact | Likely route of exposure |

Symptoms related to the physical, chemical and toxicological characteristics

INHALATION:

May cause central nervous system depression or effects. Symptoms may include headache, excitation, euphoria, dizziness, incoordination, drowsiness, light-headedness, blurred vision, fatigue, tremors, convulsions, loss of consciousness, coma, respiratory arrest and death, depending on the concentration and duration of exposure.

Breathing of the mists, vapors or fumes may irritate the nose, throat and lungs.

SKIN:

Contact may cause reddening, itching and inflammation. Prolonged skin contact may defat the skin and cause drying, cracking and/or dermatitis. Skin contact may cause harmful effects in other parts of the body.

EYES:

May cause eye irritation with tearing, redness, or a stinging or burning sensation. May cause swelling of the eyes with blurred vision. Effects may become more serious with repeated or prolonged contact.

INGESTION:

May cause irritation of the mouth, throat and gastrointestinal tract. Symptoms may include salivation, pain, nausea, vomiting and diarrhea.

Aspiration into lungs may cause chemical pneumonia and lung damage.

Information on toxicological effects

Acute toxicity Not classified.

| Components | Species | Test Results |
|--|----------------|---------------------|
| KEROSENE, STRAIGHT RUN (CAS 8008-20-6) | | |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | > 2000 mg/kg |
| Inhalation | | |
| LC50 | Rat | > 5.28 mg/l |
| Oral | | |
| LD50 | Rat | > 5000 mg/kg |

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Not classified.

Respiratory sensitization Not classified.

Skin sensitization Not classified.

Germ cell mutagenicity Not classified.

Carcinogenicity Not classified.

ACGIH Carcinogens

| | |
|---|--|
| BENZENE (CAS 71-43-2) | A1 Confirmed human carcinogen. |
| ETHYL BENZENE (CAS 100-41-4) | A3 Confirmed animal carcinogen with unknown relevance to humans. |
| KEROSENE (NON-AEROSOL), AS TOTAL HYDROCARBON VAPOR (CAS 64742-81-0) | A3 Confirmed animal carcinogen with unknown relevance to humans. |
| KEROSENE (NON-AEROSOL), AS TOTAL HYDROCARBON VAPOR (CAS 8008-20-6) | A3 Confirmed animal carcinogen with unknown relevance to humans. |
| NAPHTHALENE (CAS 91-20-3) | A3 Confirmed animal carcinogen with unknown relevance to humans. |
| TOLUENE (CAS 108-88-3) | A4 Not classifiable as a human carcinogen. |
| XYLENE (O, M AND P ISOMERS) (CAS 1330-20-7) | A4 Not classifiable as a human carcinogen. |

IARC Monographs. Overall Evaluation of Carcinogenicity

| | |
|-----------------------------|---|
| BENZENE (CAS 71-43-2) | 1 Carcinogenic to humans. |
| CUMENE (CAS 98-82-8) | 2B Possibly carcinogenic to humans. |
| ETHYLBENZENE (CAS 100-41-4) | 2B Possibly carcinogenic to humans. |
| NAPHTHALENE (CAS 91-20-3) | 2B Possibly carcinogenic to humans. |
| TOLUENE (CAS 108-88-3) | 3 Not classifiable as to carcinogenicity to humans. |
| XYLENE (CAS 1330-20-7) | 3 Not classifiable as to carcinogenicity to humans. |

US. National Toxicology Program (NTP) Report on Carcinogens

| | |
|-----------------------|-------------------------------|
| BENZENE (CAS 71-43-2) | Known To Be Human Carcinogen. |
|-----------------------|-------------------------------|

CUMENE (CAS 98-82-8)

Reasonably Anticipated to be a Human Carcinogen.

NAPHTHALENE (CAS 91-20-3)

Reasonably Anticipated to be a Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

BENZENE (CAS 71-43-2)

Cancer

Reproductive toxicity

Not classified.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

Not classified.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Toxicological data

BENZENE: Studies of workers exposed to benzene show clear evidence that overexposure can cause cancer of the blood forming organs (acute myelogenous leukemia) and aplastic anemia, an often fatal disease. Some studies suggest overexposure to benzene may also be associated with other blood disorders including myelodysplastic syndrome. Some studies of workers exposed to benzene have shown an association with increased rates of chromosome aberrations in circulating lymphocytes. One study of women workers exposed to benzene suggested a weak association with irregular menstruation. However, other studies of workers exposed to benzene have not demonstrated clear evidence of an effect on fertility or reproductive outcome in humans. Benzene can cross the placenta and affect the developing fetus. Cases of aplastic anemia have been reported in the offspring of persons severely overexposed to benzene. Animal studies indicate that prolonged, repeated exposure to high levels of benzene vapor can cause bone marrow suppression and cancer in multiple organ systems. Studies in laboratory animals also show evidence of adverse effects on male reproductive organs following high levels of exposure but no significant effects on reproduction have been observed. Embryotoxicity has been reported in studies of laboratory animals but effects were limited to reduced fetal weight and skeletal variations has been classified as a known human carcinogen by OSHA and a Group 1 (carcinogenic to Humans) material by IARC, the International Agency for Research on Cancer.

CUMENE: Overexposure to cumene may cause upper respiratory tract irritation and CNS depression. Studies in laboratory animals indicate evidence of respiratory tract hyperplasia, and adverse effects on the liver, kidney and adrenal glands following high level exposure. The relevance of these findings to humans is not clear at this time. Findings from lifetime inhalation studies in laboratory rodents were as follows: In rats, an increased incidence of renal carcinomas and adenomas, respiratory epithelial adenomas, and interstitial cell adenomas of the testes were observed. In mice, an increased incidence of carcinomas and adenomas of the bronchi and lung, liver neoplasms, hemangiosarcomas of the spleen, and adenomas of the thyroid were observed. IARC has classified cumene as "possibly carcinogenic to humans" (Group 2B) and NTP classified it as "reasonably anticipated to be a human carcinogen".

ETHYLBENZENE: Findings from a 2-year inhalation study in rodents conducted by NTP were as follows: Effects were observed only at the highest exposure level (750 ppm). At this level the incidence of renal tumors was elevated in male rats (tubular carcinomas) and female rats (tubular adenomas). The incidence of tumors was also elevated in male mice (alveolar and bronchiolar carcinomas) and female mice (hepatocellular carcinomas). IARC has classified ethyl benzene as "possibly carcinogenic to humans" (Group 2B). Studies in laboratory animals indicate some evidence of post-implantation deaths following high levels of maternal exposure. The relevance of these findings to humans is not clear at this time. Studies in laboratory animals indicate limited evidence of renal malformations, resorptions, and developmental delays following high levels of maternal exposure. The relevance of these findings to humans is not clear at this time. Studies in laboratory animals have demonstrated evidence of ototoxicity (hearing loss) following exposure levels as low as 300 ppm for 5 days. Studies in laboratory animals indicate some evidence of adverse effects on the liver, kidney, thyroid, and pituitary gland.

NAPHTHALENE: Severe jaundice, neurotoxicity (kernicterus) and fatalities have been reported in young children and infants as a result of hemolytic anemia from overexposure to naphthalene. Persons with Glucose 6-phosphate dehydrogenase (G6PD) deficiency are more prone to the hemolytic effects of naphthalene. Adverse effects on the kidney have been reported in persons overexposed to naphthalene but these effects are believed to be a consequence of hemolytic anemia, and not a direct effect. Hemolytic anemia has been observed in laboratory animals exposed to naphthalene. Laboratory rodents exposed to naphthalene vapor for 2 years (lifetime studies) developed non-neoplastic and neoplastic tumors and inflammatory lesions of the nasal and respiratory tract. Cataracts and other adverse effects on the eye have also been observed in laboratory animals exposed to high levels of naphthalene. Findings from a large number of bacterial and mammalian cell mutation assays were negative. A few studies have shown chromosomal effects (elevated levels of sister chromatid exchanges or chromosomal aberrations) in vitro. Naphthalene has been classified as possibly carcinogenic to humans (Group 2B) by IARC, the International Agency for Research on Cancer, based on findings from studies in laboratory animals.

TOLUENE: Case studies of persons abusing toluene suggest isolated incidences of adverse effects on the fetus including birth defects. Abuse of toluene at high concentrations (e.g., glue sniffing and solvent abuse) has been associated with adverse effects on the liver, kidney and nervous system, and can cause CNS depression, cardiac arrhythmias, and death. Studies of workers indicate longterm exposure may be related to impaired color vision and hearing. Some studies of workers suggest longterm exposure may be related to neurobehavioral and cognitive changes. Some of these effects have been observed in laboratory animals following repeated exposure to high levels of toluene. Several studies of workers suggest longterm exposure may be related to small increases in spontaneous abortions and changes in some gonadotropic hormones. However, the weight of evidence does not indicate toluene is a reproductive hazard to humans. Studies in laboratory animals indicate some changes in reproductive organs following high levels of exposure, but no significant effects on mating performance or reproduction were observed. Case studies of persons abusing toluene suggest isolated incidences of adverse effects on the fetus including birth defects. Findings in laboratory animals have been largely negative. Positive findings include small increases in minor skeletal and visceral malformations and developmental delays following very high levels of maternal exposure. Studies of workers indicate long-term exposure may be related to effects on the liver, kidney and blood, but these appear to be limited to changes in serum enzymes and decreased leukocyte counts. Adverse effects on the liver, kidney, thymus and nervous system were observed in animal studies following very high levels of exposure. The relevance of these findings to humans is not clear at this time.

XYLENES, ALL ISOMERS: Acute effects of xylene may be increased by the use of alcoholic beverages. Evidence of liver and kidney impairment were reported in workers recovering from a gross overexposure. Prolonged or repeated exposure to xylene was reported to cause impaired neurological function in workers exposed to solvents (including xylene). Studies in laboratory animals have shown evidence of impaired hearing following high levels of exposure. Studies in laboratory animals also suggest some changes in reproductive organs following high levels of exposure but no significant effects on reproduction were observed. Developmental toxicity studies in laboratory animals indicate skeletal and visceral malformations, developmental delays, and increased fetal resorptions following extremely high levels of maternal exposure. The relevance of these observations to humans is not clear at this time. In addition, adverse effects on the liver, kidney, bone marrow (changes in blood cell parameters) were observed in laboratory animals following high levels of exposure. The relevance of these observations to humans is not clear at this time.

C9 AROMATIC HYDROCARBONS: A developmental inhalation study in mice resulted in increased implantation losses, reduced fetal weights, delayed ossification and an increased incidence of cleft palate at the highest exposure level (1,500 ppm). This exposure level was extremely toxic to pregnant female mice (44% mortality). Reduced fetal body weights were also observed at 500 ppm. In a multi-generation reproduction inhalation study in rats, reductions in pup weights, pup weight gain, litter size, and pup survival were observed at 1,500 ppm with significant maternal toxicity. Reduced pup weight gain was also observed at 500 ppm. In general, animal studies in three species indicate that fetal effects occur at levels that are maternally toxic as well.

MIDDLE DISTILLATES, PETROLEUM: Long-term repeated (lifetime) skin exposure to similar materials has been reported to result in an increase in skin tumors in laboratory rodents. The relevance of these findings to humans is not clear at this time.

12. Ecological information

Ecotoxicity

Toxic to aquatic life with long lasting effects.

| Components | Species | | Test Results |
|--|---------|---------------|-----------------|
| KEROSENE, STRAIGHT RUN (CAS 8008-20-6) | | | |
| Acute | | | |
| Algae | EC50 | Algae | > 1 mg/l, 96 hr |
| Crustacea | EC50 | Daphnia magna | > 1 mg/l, 48 hr |
| Fish | LC50 | Fish | > 1 mg/l |
| Chronic | | | |
| Crustacea | NOEL | Daphnia magna | 0.48 mg/l |

| | |
|--------------------------------------|---|
| Persistence and degradability | Not readily biodegradable. |
| Bioaccumulative potential | May bioaccumulate in aquatic organisms. |
| Mobility in soil | May partition into air, soil and water. |
| Other adverse effects | No other adverse effects expected. |

13. Disposal considerations

| | |
|--|--|
| Disposal instructions | The transportation, storage, treatment and disposal of waste material must be conducted in compliance with federal, state, and local regulations. Under RCRA it is the responsibility of the user of the material to determine, at the time of disposal, whether this material meets RCRA criteria for hazardous waste. For additional handling information and protection of employees, see Section 7 (Handling and Storage) and Section 8 (Exposure Controls/Personal Protection). |
| Hazardous waste code | The proper waste code must be evaluated at the time of disposal and should be determined by the user and waste disposal company. |
| Waste from residues / unused products | Dispose of this material in accordance with all applicable local and national regulations. |
| Contaminated packaging | Empty containers should be taken to an approved waste handling site for recycling or disposal in accordance with government regulations. Packaging may contain residue that can be hazardous. |

14. Transport information

| | |
|---|---|
| Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code | Not classified for MARPOL. Please contact the Transportation Compliance CSO if transportation mode is ship or vessel to determine the need for a MARPOL classification. |
| General information | BILL OF LADING - BULK (U. S. DOT): See Bill of Lading for proper shipping description, or consult 49 CFR 100-185 for specific shipping information. BILL OF LADING - NON-BULK (U. S. DOT): See Bill of Lading for proper shipping description, or consult 49 CFR 100-185 for specific shipping information. Due to the possible variances of this material, the shipping classification must be evaluated at the time of shipment. Please consult 49 CFR 171 - 180 for specific shipping information. |

15. Regulatory information

| | |
|-------------------------------|--|
| US federal regulations | All ingredients are on the TSCA inventory, or are not required to be listed on the TSCA inventory. Consult OSHA's Benzene standard 29 CFR 1910.1028 for provisions on air monitoring, employee training, medical monitoring, etc. A release of this material, as supplied, may be exempt from reporting under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA - 40 CFR 302) by the petroleum exclusion. Releases may be reportable to the National Response Center (800-424-8802) under the Clean Water Act, 33 U.S.C. 1321(b)(3) and (5). This material may contain toxic chemical(s) in excess of the applicable de minimis concentration that are subject to the annual toxic chemical release reporting requirements of the Superfund Amendments and Reauthorization Act (SARA) Section 313 (40 CFR 372). This information must be included in all SDSs that are copied and distributed for this material. Check local, regional or state/provincial regulations for any additional requirements as these may be more restrictive than federal laws and regulations. Failure to comply may result in substantial civil and criminal penalties. |
|-------------------------------|--|

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

| | |
|--------------------------------------|-------|
| 1,2,4-TRIMETHYLBENZENE (CAS 95-63-6) | 1.0 % |
| BENZENE (CAS 71-43-2) | 0.1 % |
| BIPHENYL (CAS 92-52-4) | 1.0 % |

| | |
|-----------------------------|-------|
| CUMENE (CAS 98-82-8) | 1.0 % |
| ETHYLBENZENE (CAS 100-41-4) | 0.1 % |
| NAPHTHALENE (CAS 91-20-3) | 0.1 % |
| TOLUENE (CAS 108-88-3) | 1.0 % |
| XYLENE (CAS 1330-20-7) | 1.0 % |

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

| | |
|--------------------------------------|---------|
| 1,2,4-TRIMETHYLBENZENE (CAS 95-63-6) | Listed. |
| BENZENE (CAS 71-43-2) | Listed. |
| BIPHENYL (CAS 92-52-4) | Listed. |
| CUMENE (CAS 98-82-8) | Listed. |
| ETHYLBENZENE (CAS 100-41-4) | Listed. |
| NAPHTHALENE (CAS 91-20-3) | Listed. |
| TOLUENE (CAS 108-88-3) | Listed. |
| XYLENE (CAS 1330-20-7) | Listed. |

CERCLA Hazardous Substance List (40 CFR 302.4)

| | |
|-----------------------------|--------|
| BENZENE (CAS 71-43-2) | LISTED |
| BIPHENYL (CAS 92-52-4) | LISTED |
| CUMENE (CAS 98-82-8) | LISTED |
| ETHYLBENZENE (CAS 100-41-4) | LISTED |
| NAPHTHALENE (CAS 91-20-3) | LISTED |
| TOLUENE (CAS 108-88-3) | LISTED |
| XYLENE (CAS 1330-20-7) | LISTED |

US CERCLA Hazardous Substances: Reportable quantity

| | |
|-----------------------------|----------|
| BENZENE (CAS 71-43-2) | 10 LBS |
| BIPHENYL (CAS 92-52-4) | 100 LBS |
| CUMENE (CAS 98-82-8) | 5000 LBS |
| ETHYLBENZENE (CAS 100-41-4) | 1000 LBS |
| NAPHTHALENE (CAS 91-20-3) | 100 LBS |
| TOLUENE (CAS 108-88-3) | 1000 LBS |
| XYLENE (CAS 1330-20-7) | 100 LBS |

US EPCRA (SARA Title III) Section 304 - Extremely Hazardous Spill: Reportable quantity

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

| | |
|-----------------------|--|
| BENZENE (CAS 71-43-2) | Cancer Central nervous system Blood Aspiration Skin Eye respiratory tract irritation Flammability |
|-----------------------|--|

Superfund Amendments and Reauthorization Act of 1986 (SARA)

| | |
|--------------------------|---|
| Hazard categories | Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No |
|--------------------------|---|

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

| |
|-----------------------------|
| BENZENE (CAS 71-43-2) |
| BIPHENYL (CAS 92-52-4) |
| CUMENE (CAS 98-82-8) |
| ETHYLBENZENE (CAS 100-41-4) |
| NAPHTHALENE (CAS 91-20-3) |
| TOLUENE (CAS 108-88-3) |
| XYLENE (CAS 1330-20-7) |

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

US. California Proposition 65

WARNING: This product contains one or more chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Proposition 65, CAL. HSC. §25249.5.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

| | |
|-----------------------|---------------------------|
| BENZENE (CAS 71-43-2) | Listed: February 27, 1987 |
|-----------------------|---------------------------|

CUMENE (CAS 98-82-8) Listed: April 6, 2010
ETHYLBENZENE (CAS 100-41-4) Listed: June 11, 2004
NAPHTHALENE (CAS 91-20-3) Listed: April 19, 2002

US - California Proposition 65 - CRT: Listed date/Developmental toxin

BENZENE (CAS 71-43-2) Listed: December 26, 1997
TOLUENE (CAS 108-88-3) Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

TOLUENE (CAS 108-88-3) Listed: August 7, 2009

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

BENZENE (CAS 71-43-2) Listed: December 26, 1997

16. Other information, including date of preparation or last revision

Issue date 12-19-2014

Version # 01

Further information WARNING: THIS PRODUCT, AS INDICATED, CONTAINS BIODIESEL. BIODIESEL, OR FUELS BLENDED WITH BIODIESEL, MAY UNDER CERTAIN COLD WEATHER CONDITIONS GEL, CLOG, DAMAGE OR HARM FUEL STORAGE TANKS, PIPING, METERS, DIESEL ENGINES AND/OR RELATED FUEL SYSTEMS (INCLUDING, BUT NOT LIMITED TO MARINE EQUIPMENT). IT IS IMPERATIVE THAT BEFORE YOU USE OR STORE THIS PRODUCT YOU CONDUCT AN ASSESSMENT TO DETERMINE WHETHER THIS FUEL IS COMPATIBLE WITH YOUR PARTICULAR EQUIPMENT/MACHINERY IN WHICH THIS FUEL MIGHT BE STORED, TRANSPORTED OR COMBUSTED. AS SOME MANUFACTURERS MAY VOID ENGINE WARRANTIES IF THIS FUEL IS USED, IT IS IMPORTANT YOU REVIEW THE TERMS OF YOUR MANUFACTURER'S WARRANTY AND DETERMINE IF THIS FUEL IS RIGHT FOR YOUR APPLICATION.

DISCLAIMER OF ALL WARRANTIES: Fauser Energy RESOURCES MAKES NO WARRANTY EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR WARRANTY FOR FITNESS FOR ANY PARTICULAR PURPOSE AND HEREBY DISCLAIMS ALL SUCH WARRANTIES REGARDING THIS PRODUCT.

HMIS® ratings Health: 1*
Flammability: 2
Physical hazard: 0
* Indicates chronic health hazard

NFPA ratings Health: 1
Flammability: 2
Instability: 0

Disclaimer THIS SDS HAS BEEN PREPARED TO COMPLY WITH FEDERAL REGULATIONS THAT ARE INTENDED TO QUICKLY PROVIDE USEFUL INFORMATION TO THE USER(S) OF THIS MATERIAL OR PRODUCT - IT IS NOT INTENDED TO SERVE AS A COMPREHENSIVE DISCUSSION OF ALL POSSIBLE RISKS OF HAZARDS, BUT RATHER PROVIDES INFORMATION GENERALLY ACCEPTED IN THE SCIENTIFIC COMMUNITY AS RELEVANT REGARDING THE POTENTIAL HAZARDS OF THIS PRODUCT. ADEQUATE TRAINING, INSTRUCTION, WARNINGS AND SAFE HANDLING PROCEDURES SHOULD BE PROVIDED TO HANDLERS AND USERS. USERS SHOULD REVIEW THE INFORMATION IN THE SDS, AND SATISFY THEMSELVES AS TO ITS SUITABILITY AND COMPLETENESS, INCLUDING ENSURING THAT THIS IS THE MOST CURRENT SDS.

Revision Information Product and Company Identification: Synonyms
Composition / Information on Ingredients: Ingredients
Physical & Chemical Properties: Multiple Properties
Transport Information: Material Transportation Information
HazReg Data: International Inventories

Completed by Fauser Energy Resources